NSN 5930-01-358-8501

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-358-8501

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and moisture resistant and salt spray resistant and shock resistant and vibration resistant
Overall Length:
2.330 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
0.960 inches
Case Material:
Metal
Actuator Length:
0.510 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.510 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Yellow single actuator
Actuator Inscription:
Master caution single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-358-8501

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0