

View Online at <https://aerobasegroup.com/nsn/5930-01-359-1430>

**Thread Class:**

3a all pressure connection

**Overall Length:**

3.057 inches

**Outside Diameter:**

0.438 inches all connections

**Overall Width:**

2.110 inches

**Overall Diameter:**

Between 1.000 inches and 1.600 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Inlet connection and outlet connection

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

250.00 pounds per square inch gage

**Thread Size:**

0.438 inches all pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

4.0 amperes resistive load single voltage and 2.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

17.50 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Test Data Document:**

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf all pressure connection

**Specification Data:**

81349-mil-s09395/29 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0