NSN 5930-01-359-1994

Sensitive Switch - Page 1 of 2

Between 0.370 inches and 0.380 inches

Thread Class:

Body Style:Hole mounted

Overall Height:

2b



View Online at https://aerobasegroup.com/nsn/5930-01-359-1994

Center To Center Distance Between Mounting Facilities Parallel To Length:

Body Length: 0.940 inches Body Width: 0.370 inches Actuator Style: Round Actuator Free Position Height:
Body Width: 0.370 inches Actuator Style: Round Actuator Free Position Height:
0.370 inches Actuator Style: Round Actuator Free Position Height:
Actuator Style: Round Actuator Free Position Height:
Round Actuator Free Position Height:
Actuator Free Position Height:
Patrician 0.700 inches and 0.000 inches
Between 0.760 inches and 0.820 inches
Actuator Adapter Style:
Roller leaf
Maximum Voltage Rating In Volts:
30.0 dc and 250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Screw
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:
Between 0.015 overtravel inches and 0.025 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 wire lead

NSN 5930-01-359-1994

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0