# NSN 5930-01-359-1994

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-359-1994

#### **Thread Class:**

2b

# Body Style:

Hole mounted

# Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

## **Overall Height:**

1.105 inches

#### **Body Length:**

0.940 inches

#### **Body Width:**

0.370 inches

#### **Actuator Style:**

Round

#### **Actuator Free Position Height:**

Between 0.760 inches and 0.820 inches

## Actuator Adapter Style:

Roller leaf

#### Maximum Voltage Rating In Volts:

30.0 dc and 250.0 ac

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Screw

#### Thready Qty Per Inch (tpi):

56

## Thread Size:

0.086 inches

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

2.0 ounces

#### Switch Actuating Force:

12.0 ounces

#### Actuator Movement:

Between 0.015 overtravel inches and 0.025 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

# **Thread Series Designator:**

Unc

#### **Terminal Type And Quantity:**

3 wire lead

# NSN 5930-01-359-1994

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

