## NSN 5930-01-359-4125

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-359-4125

| Hazardous Locations/environmental Protection:   |
|---|
| Corrosion resistant   |
| Overall Length:   |
| 1.375 inches  |
| Outside Diameter:   |
| 0.125 inches single connection  |
| Overall Height:   |
| 1.938 inches  |
| Overall Width:  |
| 1.250 inches  |
| Pressure Switch Type:   |
| Gage  |
| Mounting Method:  |
| Input port  |
| Contact Action Stimulus:  |
| Increase  |
| Thread Size:  |
| 0.125 inches single pressure connection   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary  |
|   |
| Terminal Type:  |
| Quick disconnect, male  |
| Contact Load Current Rating:  |
| 4.0 amperes resistive load first voltage5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage |
| Contact Adjustability:  |
| Actuation point adjustable  |
| Contact Adjustment Range:   |
| +2.00/+100.00 actuation point pounds per square inch gage   |
| Contact Adjustment Type:  |
| External actuation point hex nut  |
| Contact Voltage Rating In Volts:  |
| 250.0 ac at sea level first voltage28.0 dc at sea level second voltage  |
| Pressure Connector Type:  |
| Swivel nut, flared, threaded external single connection   |
| Media For Which Designed:   |
| Gas or liquid   |
| Precious Material And Location:   |
| Contacts silver   |
| Precious Material:  |
| Silver  |
| Style Designator:   |

Cylindrical w/lugs

## NSN 5930-01-359-4125

Pressure Switch - Page 2 of 2



| Thread | <b>Series</b> | Design | ator |
|--------|---------------|--------|------|
|        |               |        |      |

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0