## NSN 5930-01-359-4125

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-359-4125

Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
1.375 inches
Outside Diameter:
0.125 inches single connection
Overall Height:
1.938 inches
Overall Width:
1.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Input port
Contact Action Stimulus:
Increase
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
4.0 amperes resistive load first voltage5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+2.00/+100.00 actuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point hex nut
Contact Voltage Rating In Volts:
250.0 ac at sea level first voltage28.0 dc at sea level second voltage
Pressure Connector Type:
Swivel nut, flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:

Cylindrical w/lugs

## NSN 5930-01-359-4125

Pressure Switch - Page 2 of 2



Thread	<b>Series</b>	Design	ator

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0