NSN 5930-01-359-4127

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-359-4127

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
3.062 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Flangewidth:
1.438 inches
Tempurature Sensing Element Type:
Expanding shell
Mounting Facility Circle Radius:
0.625 inches
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage1.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
150.00 actuation point degrees fahrenheit
Contact Voltage Rating In Volts:
115.0 ac at sea level first voltage32.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5930-01-359-4127

Thermostatic Switch - Page 2 of 2

Fiig: A048b0

