

View Online at <https://aerobasegroup.com/nsn/5930-01-359-5452>

**Outside Diameter:**

0.313 inches all connections

**Unthreaded Mounting Hole Diameter:**

0.170 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.500 inches

**Longest Vertical Distance Between Mounting Centers:**

4.500 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

15.00 inches of water

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Turret

**Contact Load Current Rating:**

4.0 amperes resistive load first voltage 5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Type:**

External actuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage 28.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, unthreaded external all connections

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0