

View Online at <https://aerobasegroup.com/nsn/5930-01-359-5452>

Outside Diameter:

0.313 inches all connections

Unthreaded Mounting Hole Diameter:

0.170 inches

Longest Horizontal Distance Between Mounting Centers:

3.500 inches

Longest Vertical Distance Between Mounting Centers:

4.500 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

15.00 inches of water

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

4.0 amperes resistive load first voltage 5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Type:

External actuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, unthreaded external all connections

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0