

View Online at <https://aerobasegroup.com/nsn/5930-01-359-5457>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

1.340 inches

**Body Width:**

1.660 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.690 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.370 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

11.000 amperes resistive ac and 8.000 amperes inductive ac and 8.000 amperes lamp ac and 18.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc

**Test Data Document:**

82348-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Specification Data:**

96906-ms27736-31 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0