

View Online at <https://aerobasegroup.com/nsn/5930-01-359-5462>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Explosion proof and flame resistant and fungus resistant and moisture resistant

Overall Length:

2.070 inches

Body Diameter:

0.750 inches

Bushing Length:

0.440 inches

Body Length:

0.980 inches

Overall Diameter:

0.750 inches

Case Material:

Metal

Actuator Style:

Round, threaded

Actuator Height:

0.400 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Mounting hardware and rfi shielding

Thready Qty Per Inch (tpi):

32

Thread Size:

0.5625 inches

Nonpile-up Contact Arrangement:

6 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc

Precious Material And Location:

Contacts silver

Thread Series Designator:

Un

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0