NSN 5930-01-359-7145

Rotary Switch - Page 1 of 2



Trotary Switch Tage For 2
View Online at https://aerobasegroup.com/nsn/5930-01-359-7145
Overall Length:
6.337 inches
Overall Height:
2.625 inches
Overall Width:
2.312 inches
Shaft Length:
2.562 inches single actuator
Unthreaded Mounting Hole Diameter:
0.250 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.876 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.688 inches single mounting facility
End Application:
Switchboard s/s 200 kw part number 104te6201-25 aboard 180 ft wlb coast guard vessels
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section periphery
Throw Quantity:
2 single section periphery
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated
Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-01-359-7145

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Largest Shaft Width:

0.250 inches single actuator

Special Features:

Spring return not included

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0