## NSN 5930-01-359-9049

Pressure Switch - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5930-01-359-9049   |
|---|
| Inside Diameter:  |
| 0.250 inches single connection  |
| Hazardous Locations/environmental Protection:   |
| Waterproof  |
| Overall Length:   |
| 2.415 inches  |
| Body Length:  |
| 1.500 inches  |
| Overall Diameter:   |
| 0.820 inches  |
| Pressure Switch Type:   |
| Gage  |
| Mounting Method:  |
| Input port  |
| Contact Action Stimulus:  |
| Increase  |
| Proof Pressure:   |
| 600.00 pounds per square inch   |
| Thread Size:  |
| 0.250 inches single pressure connection   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally closed, momentary action   |
| Terminal Type:  |
| Wire lead   |
| Contact Load Current Rating:  |
| 2.0 amperes resistive load single voltage   |
| Contact Adjustability:  |
| Actuation point not adjustable and deactuation point not adjustable   |
| Contact Stimulus Rating:  |
| 400.00 actuation point pounds per square inch gage and 300.00 deactuation point pounds per square inch gage |
| Contact Voltage Rating In Volts:  |
| 28.0 dc at sea level single voltage   |
| Pressure Connector Type:  |
| Swivel nut, inverted flare, threaded internal single connection   |
| Media For Which Designed:   |
| Gas or liquid   |
| Style Designator:   |
| Cylindrical   |
| Thread Series Designator:   |
| Npt single pressure connection  |

Shelf Life: N/a

## NSN 5930-01-359-9049

Pressure Switch - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A048b0