NSN 5930-01-360-1484

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-360-1484 **Overall Height:** 2.500 inches **Overall Width:** 2.625 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.876 inches single mounting facility **Shortest Vertical Distance Between Mounting Centers:** 1.688 inches single mounting facility **End Application:** Switchboard s/s 200 kw p/n 104te6201-25 used onboard 180 ft wlb coast guard vessels **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section periphery **Throw Quantity:** 1 single section periphery **Features Provided:** Actuator knob and spring return **Contact Voltage Rating In Volts:** 600.0 ac at sea level600.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 20.0 amperes resistive load ac at sea level20.0 amperes resistive load dc at sea level **Style Designator:** In-line, cam actuated Shelf Life: N/a **Unit Of Measure:**

--

NSN 5930-01-360-1484

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0