

View Online at <https://aerobasegroup.com/nsn/5930-01-360-3151>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

0.900 inches

Body Diameter:

0.562 inches

Bushing Length:

0.260 inches

Body Length:

0.237 inches

Overall Diameter:

0.562 inches

Actuator Style:

Round

Actuator Diameter:

0.190 inches

Actuator Height:

0.125 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

0.3 dc

End Application:

6020-01-237-2218 converter fiber

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Full display lens

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.0 milliamperes resistive dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-8805/110 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0