NSN 5930-01-360-6166

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-360-6166

View Online at https://aerobasegroup.com/nsn/5930-01-360-6166
Overall Length:
11.340 inches
Overall Height:
2.910 inches
Overall Width:
2.810 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
12
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
350.0 dc at sea level500.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Screw
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
400.0 milliamperes inductive load ac at sea level400.0 milliamperes inductive load dc at sea level5.0 amperes inductive load highest ac
voltage rating at sea level20.0 amperes inductive load lowest ac voltage rating at sea level
Special Features:
Legend plate engraved w/off; 2; 3; 4; 5; 6; 7; 8
Precious Material And Location:
Terminal and rotors silver

Silver

Style Designator:

Precious Material:

Tap, circuit selector

NSN 5930-01-360-6166

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0