## NSN 5930-01-360-8155

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-360-8155

Body Style:
Printed circuit
Overall Length:
1.080 inches
Overall Height:
0.175 inches
Overall Width:
0.300 inches
Body Length:
1.080 inches
Body Width:
0.286 inches
Body Height:
0.180 inches
Switch Actuator Quantity:
10
Actuator Style:
Rectangular
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
24.0 dc
Mounting Method:
Printed circuit
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained 1st switch unit1 pole, single throw, both positions maintained 2nd switch unit1 pole, single
throw, both positions maintained 3rd switch unit1 pole, single throw, both positions maintained 4th switch unit1 pole, single throw, both
positions maintained 5th switch unit1 pole, single throw, both positions maintained 6th switch unit1 pole, single throw, both positions
maintained 7th switch unit1 pole, single throw, both positions maintained 8th switch unit1 pole, single throw, both positions maintained 9th
switch unit1 pole, single throw, both positions maintained 10th switch unit
Contact Load Current Rating At Maximum Rated Voltage:
25.0 milliamperes resistive dc
Special Features:
Actuators are recessed
Test Data Document:
81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

20 printed circuit

## **Specification Data:**

81349-mil-s-83504/12 government specification

Shelf Life:

N/a

## **NSN 5930-01-360-8155** Slide Switch - Page 2 of 2



Fiig:

A053a0