

View Online at <https://aerobasegroup.com/nsn/5930-01-360-8155>

**Body Style:**

Printed circuit

**Overall Length:**

1.080 inches

**Overall Height:**

0.175 inches

**Overall Width:**

0.300 inches

**Body Length:**

1.080 inches

**Body Width:**

0.286 inches

**Body Height:**

0.180 inches

**Switch Actuator Quantity:**

10

**Actuator Style:**

Rectangular

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

24.0 dc

**Mounting Method:**

Printed circuit

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained 1st switch unit 1 pole, single throw, both positions maintained 2nd switch unit 1 pole, single throw, both positions maintained 3rd switch unit 1 pole, single throw, both positions maintained 4th switch unit 1 pole, single throw, both positions maintained 5th switch unit 1 pole, single throw, both positions maintained 6th switch unit 1 pole, single throw, both positions maintained 7th switch unit 1 pole, single throw, both positions maintained 8th switch unit 1 pole, single throw, both positions maintained 9th switch unit 1 pole, single throw, both positions maintained 10th switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.0 milliamperes resistive dc

**Special Features:**

Actuators are recessed

**Test Data Document:**

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Specification Data:**

81349-mil-s-83504/12 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

A053a0