NSN 5930-01-360-8709

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-360-8709

Body Style: Printed circuit Overall Length: 0.620 inches Overall Height: 1.087 inches Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained Maximum Voltage Rating In Volts:						
Overall Length: 0.620 inches Overall Height: 1.087 inches Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Overall Height: 1.087 inches Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Overall Height: 1.087 inches Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
1.087 inches Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Overall Width: 0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.365 inches Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Body Length: 0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.500 inches Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Body Width: 0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.450 inches Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Body Height: 0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.460 inches Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Actuator Length: 0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.531 inches Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Actuator Style: Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Pivoted Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Actuator Height: 0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.310 inches Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Actuator Width: 0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
0.356 inches Actuator Position-action Relationship: Left position maintained and right position maintained						
Actuator Position-action Relationship: Left position maintained and right position maintained						
Left position maintained and right position maintained						
Maximum Voltage Rating In Volts:						
3						
120.0 dc and 250.0 ac						
End Application:						
6625-01-206-5398 semicondutor test						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Printed circuit						
Nonpile-up Contact Arrangement:						
2 pole, double throw, both positions maintained single switch unit						
Contact Load Current Rating At Maximum Rated Voltage:						
5.000 amperes resistive dc and 2.000 amperes resistive ac						
Precious Material And Location:						
Contact and terminal srufaces silver						
Contact and terminal sidiaces sliver						
Terminal Type And Quantity:						

N/a

NSN 5930-01-360-8709 Toggle Switch - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A053a0