

View Online at <https://aerobasegroup.com/nsn/5930-01-361-0114>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

0.575 inches

**Body Width:**

0.535 inches

**Body Height:**

0.640 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.690 inches

**Actuator Position-action Relationship:**

Up position maintained and center position maintained and down position momentary

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.740 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes lamp ac and 5.000 amperes resistive ac and 2.000 amperes inductive ac

**Test Data Document:**

25778-105716 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0