

View Online at <https://aerobasegroup.com/nsn/5930-01-361-0457>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

Between 2.095 inches and 2.105 inches

Body Diameter:

Between 0.615 inches and 0.650 inches

Bushing Length:

0.360 inches

Body Length:

1.280 inches

Overall Diameter:

Between 0.615 inches and 0.650 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

0.270 inches

Actuator Color:

Red single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Full display lens

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 500.0 milliamperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 500.0 milliamperes lamp ac

Test Data Document:

81349-mil-prf-22885/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-prf-22885/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.