

View Online at <https://aerobasegroup.com/nsn/5930-01-361-6335>

Hazardous Locations/environmental Protection:

Salt spray resistant and vibration resistant

Overall Length:

0.345 inches

Overall Height:

0.080 inches

Body Diameter:

0.263 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 365.0 degrees fahrenheit

Mounting Method:

Surface and terminal

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load first voltage 1.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

210.00 actuation point degrees fahrenheit and 180.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage 60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0