NSN 5930-01-362-5618

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-362-5618

3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant
Body Width:
1.200 inches
Body Height:
0.960 inches
Actuator Length:
1.404 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
Between 0.835 inches and 0.865 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator and yellow single actuator
Actuator Inscription:
Select/sine, waveform single actuator
Illuminated Actuator Color Sequence:
Top half white bottom half yellow
Maximum Voltage Rating In Volts:
30.0 dc
End Application:
An/spg-51c
Mounting Surface To Terminal End Distance:
2.970 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens and lamp holder and removable light filter
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc

Contacts gold

Precious Material And Location:

NSN 5930-01-362-5618

Push Switch - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity
----------------------------	----------	------	-----	----------

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0