NSN 5930-01-362-9707

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-362-9707

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant

Body Width:

1.200 inches

Body Height:

0.960 inches

Case Material:

Metal

Actuator Length:

1.040 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

Between 0.835 inches and 0.865 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and yellow single actuator and yellow single actuator and green single actuator

Actuator Inscription:

Range, ambiguity single actuator

Illuminated Actuator Color Sequence:

Upper left green upper right yellow lower left yellow lower right green

Maximum Voltage Rating In Volts:

30.0 dc

End Application:

An/spg-51c

Mounting Surface To Terminal End Distance:

2.970 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens and lamp holder and removable light filter

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-362-9707

Push Switch - Page 2 of 2



Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0