NSN 5930-01-362-9709

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-362-9709

| 3, 2 - 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, |
|--|
| Body Style: |
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Shock resistant |
| Body Width: |
| 1.200 inches |
| Body Height: |
| 0.960 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 1.040 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.140 inches |
| Actuator Width: |
| Between 0.835 inches and 0.865 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Yellow single actuator |
| Actuator Inscription: |
| Cross-pol, narrow / side lobe, noise narrow single actuator |
| Illuminated Actuator Color Sequence: |
| All yellow |
| Maximum Voltage Rating In Volts: |
| 30.0 dc |
| End Application: |
| An/spg-51c |
| Mounting Surface To Terminal End Distance: |
| 2.970 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Horizontal split lens and lamp holder and removable light filter |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-362-9709

Push Switch - Page 2 of 2



| Precious Material And Location: |
|--|
| Contacts gold |
| Terminal Type And Quantity: |
| 6 turret and 5 tab, solder lug |
| Shelf Life: |
| N/a |

Demilitarization:

Unit Of Measure:

No

Fiig:

A053a0