## NSN 5930-01-362-9712

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-362-9712

## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Shock resistant

## **Body Width:**

1.200 inches

#### **Body Height:**

0.960 inches

#### **Case Material:**

Metal

#### Actuator Length:

1.040 inches

#### **Actuator Style:**

Rectangular

#### **Actuator Height:**

0.140 inches

#### Actuator Width:

Between 0.835 inches and 0.865 inches

#### Actuator Color:

White single actuator

## Illuminated Actuator Color:

White single actuator and white single actuator and yellow single actuator and yellow single actuator

#### **Actuator Inscription:**

Select / main lobe, noise narrow single actuator

#### Illuminated Actuator Color Sequence:

Top half white bottom half yellow

#### Maximum Voltage Rating In Volts:

30.0 dc

#### End Application:

An/spg-51c

## Mounting Surface To Terminal End Distance:

2.970 inches

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Horizontal split lens and lamp holder and removable light filter

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

# NSN 5930-01-362-9712

Push Switch - Page 2 of 2



**Precious Material And Location:** 

Contacts gold

## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0