

View Online at <https://aerobasegroup.com/nsn/5930-01-363-4231>

**Overall Length:**

Between 1.160 inches and 1.260 inches

**Overall Height:**

0.526 inches

**Body Diameter:**

Between 0.560 inches and 0.640 inches

**Mounting Slot Width:**

Between 0.133 inches and 0.147 inches

**Body Height:**

Between 0.366 inches and 0.431 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.133 inches and 0.147 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load first voltage and 1.0 amperes inductive load first voltage and 0.5 amperes lamp load first voltage  
2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

146.00 actuation point degrees fahrenheit and 154.00 actuation point degrees fahrenheit and 126.00 deactuation point degrees fahrenheit  
and 134.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage  
28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-24236/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0