

View Online at <https://aerobasegroup.com/nsn/5930-01-363-4235>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.350 inches

Body Length:

0.500 inches

Body Width:

0.270 inches

Body Height:

0.350 inches

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position momentary

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc or 120.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Terminals gold and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0