

View Online at <https://aerobasegroup.com/nsn/5930-01-363-5684>

Thread Class:

2a 4th mounting facility

Overall Length:

6.500 inches

Overall Diameter:

2.000 inches

Distance Between Mounting Facility Centers:

1.641 inches 4th mounting facility

Individual Section Quantity:

10

End Application:

Rotary switch used on electrical panel onboard 378 ft whec coast guard vessels

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

10 each section in-line

Throw Quantity:

7 each section periphery

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Thread Size:

6.570 inches 4th mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Rotor Through Connection Quantity:

10 10th section

Mounting Facility Pattern:

Four position diamond 4th mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks, breaks before makes each section in-line

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level

Special Features:

Shorting contact

Style Designator:

Circular, cam actuated

Thread Series Designator:

Unf 4th mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0