

View Online at <https://aerobasegroup.com/nsn/5930-01-363-6317>

Thread Class:

2a

Body Style:

Hole mount

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.460 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

1.420 inches

Actuator Length:

0.570 inches

Actuator Style:

Rectangular

Actuator Height:

0.570 inches

Actuator Width:

0.870 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position momentary

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes inductive dc and 15.000 amperes inductive ac and 5.000 amperes lamp dc and 5.000 amperes lamp ac and 20.000 amperes resistive dc and 20.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0