

View Online at <https://aerobasegroup.com/nsn/5930-01-363-7035>

**Thread Class:**

2b

**Body Style:**

Hole mount

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.625 inches

**Body Width:**

0.718 inches

**Body Height:**

1.820 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position locked in

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel and threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes inductive dc and 8.000 amperes inductive ac and 5.000 amperes lamp dc and 2.000 amperes lamp ac and 18.000 amperes resistive dc and 11.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0