

View Online at <https://aerobasegroup.com/nsn/5930-01-363-7036>

Thread Class:

2a

Body Style:

Hole mount

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches

Body Length:

0.830 inches

Body Width:

0.718 inches

Body Height:

1.820 inches

Actuator Style:

Rectangular

Actuator Width:

0.648 inches

Actuator Position-action Relationship:

Down position momentary and center position maintained

Actuator Position-locking Relationship:

Down position locked in and center position locked in

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Panel and threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive dc and 8.000 amperes inductive ac and 5.000 amperes lamp dc and 2.000 amperes lamp ac and 18.000 amperes resistive dc and 11.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0