

View Online at <https://aerobasegroup.com/nsn/5930-01-364-4719>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

4.575 inches

**Overall Diameter:**

1.170 inches

**Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:**

8

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section in-line

**Throw Quantity:**

9 each section in-line

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.437 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level115.0 highest dc voltage rating at sea level6.0 lowest dc voltage rating at sea level

**Rotor Through Connection Quantity:**

8 each section

**Switch Actuator Indexing Position Quantity:**

9 all actuators

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section in-line

**Switch Actuator Positioning Increment:**

30.0 degrees all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level and 0.25 amperes inductive load ac at sea level0.10 amperes resistive load highest dc voltage rating at sea level and 0.02 amperes inductive load highest dc voltage rating at sea level1.0 amperes resistive load lowest dc voltage rating at sea level and 0.10 amperes inductive load lowest dc voltage rating at sea level

**Precious Material And Location:**

Terminals silver and contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0