

View Online at <https://aerobasegroup.com/nsn/5930-01-364-4719>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.575 inches

Overall Diameter:

1.170 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

8

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section in-line

Throw Quantity:

9 each section in-line

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.437 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level115.0 highest dc voltage rating at sea level6.0 lowest dc voltage rating at sea level

Rotor Through Connection Quantity:

8 each section

Switch Actuator Indexing Position Quantity:

9 all actuators

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section in-line

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level and 0.25 amperes inductive load ac at sea level0.10 amperes resistive load highest dc voltage rating at sea level and 0.02 amperes inductive load highest dc voltage rating at sea level1.0 amperes resistive load lowest dc voltage rating at sea level and 0.10 amperes inductive load lowest dc voltage rating at sea level

Precious Material And Location:

Terminals silver and contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0