NSN 5930-01-364-9296

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-364-9296

Thread Class: 2a single threaded bushing **Overall Length:** 0.455 inches **Body Length:** 0.290 inches **Tempurature Sensing Element Type:** Disc Width Across Flats: 0.215 inches **Operating Tempurature Rating:** Between -30.0 degrees fahrenheit and 400.0 degrees fahrenheit **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 single threaded bushing **Contact Action Stimulus:** Decrease **Thread Size:** 0.112 inches single threaded bushing **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 1.0 amperes resistive load first voltage1.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point not adjustable **Contact Stimulus Rating:** 260.00 deactuation point degrees fahrenheit and 230.00 actuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 115.0 ac at sea level first voltage28.0 dc at sea level second voltage Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid **Style Designator:** Plug **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single threaded bushing

NSN 5930-01-364-9296

Thermostatic Switch - Page 2 of 2



_				
C r	nacit	icat	ion	Data:
O L	75 011	ıvaı	IUII	vala.

81349-mil-s-24236/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0