

View Online at <https://aerobasegroup.com/nsn/5930-01-364-9296>

Thread Class:

2a single threaded bushing

Overall Length:

0.455 inches

Body Length:

0.290 inches

Temperature Sensing Element Type:

Disc

Width Across Flats:

0.215 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40 single threaded bushing

Contact Action Stimulus:

Decrease

Thread Size:

0.112 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load first voltage 1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable

Contact Stimulus Rating:

260.00 deactuation point degrees fahrenheit and 230.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Plug

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single threaded bushing

Specification Data:

81349-mil-s-24236/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0