

View Online at <https://aerobasegroup.com/nsn/5930-01-365-6388>

**Body Style:**

Panel mounted

**Body Width:**

0.875 inches

**Body Height:**

0.875 inches

**Actuator Length:**

0.700 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.270 inches

**Actuator Width:**

0.700 inches

**Illuminated Actuator Color:**

Green single actuator

**Actuator Inscription:**

Power on single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

2.430 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.500 amperes inductive dc and 2.000 amperes inductive ac and 4.000 amperes lamp dc and 7.000 amperes lamp ac and 7.000 amperes resistive dc and 7.000 amperes resistive ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab, solder lug and 3 turret

**Specification Data:**

81349-mil-s-22885/84 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0