## NSN 5930-01-365-6388

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-01-365-6366
Body Style:
Panel mounted
Body Width:
0.875 inches
Body Height:
0.875 inches
Actuator Length:
0.700 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.700 inches
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Power on single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
2.430 inches
Inclosure Type:
Uninclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.500 amperes inductive dc and 2.000 amperes inductive ac and 4.000 amperes lamp dc and 7.000 amperes lamp ac and 7.000 amperes
resistive dc and 7.000 amperes resistive ac
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 tab, solder lug and 3 turret
Specification Data:
81349-mil-s-22885/84 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

## NSN 5930-01-365-6388

Push Switch - Page 2 of 2



Fiig:

A053a0