

View Online at <https://aerobasegroup.com/nsn/5930-01-365-9614>

**Body Style:**

Bushing mount

**Overall Length:**

Between 1.418 inches and 1.498 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

Between 1.230 inches and 1.270 inches

**Body Width:**

0.635 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.660 inches and 0.720 inches

**Actuator Position-action Relationship:**

Left position momentary and right position momentary and center position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Nsn 6115-01-296-1463; generator set, diesel engine

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Pile-up Contact Form Arrangement:**

A1 single position

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes lamp ac and 4.000 amperes lamp dc and 11.000 amperes resistive ac and 15.000 amperes resistive dc and 7.000 amperes inductive ac and 10.000 amperes inductive dc

**Terminal Type And Quantity:**

3 tab w/screw

**Specification Data:**

30554 - 88-21081 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0