

View Online at <https://aerobasegroup.com/nsn/5930-01-365-9614>

Body Style:

Bushing mount

Overall Length:

Between 1.418 inches and 1.498 inches

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

Between 1.230 inches and 1.270 inches

Body Width:

0.635 inches

Actuator Style:

Round

Actuator Height:

Between 0.660 inches and 0.720 inches

Actuator Position-action Relationship:

Left position momentary and right position momentary and center position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Nsn 6115-01-296-1463; generator set, diesel engine

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Pile-up Contact Form Arrangement:

A1 single position

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes lamp ac and 4.000 amperes lamp dc and 11.000 amperes resistive ac and 15.000 amperes resistive dc and 7.000 amperes inductive ac and 10.000 amperes inductive dc

Terminal Type And Quantity:

3 tab w/screw

Specification Data:

30554 - 88-21081 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0