

View Online at <https://aerobasegroup.com/nsn/5930-01-367-5391>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.343 inches

Bushing Length:

0.282 inches

Body Length:

0.628 inches

Actuator Style:

Round

Actuator Diameter:

0.156 inches

Actuator Height:

0.136 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes inductive dc and 5.000 amperes resistive dc and 2.000 amperes inductive ac and 5.000 amperes resistive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-8805/96 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0