

View Online at <https://aerobasegroup.com/nsn/5930-01-367-9343>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

5.175 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Shaft Diameter:

0.250 inches all actuators

Shaft Length:

0.688 inches all actuators

Individual Section Quantity:

6

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 each section front

Throw Quantity:

8 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise all actuators

Rotor Through Connection Quantity:

8 each section

Switch Actuator Indexing Position Quantity:

8 all actuators

Shaft Type:

Round all actuators

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

50.0 milliamperes inductive load ac at sea level and 125.0 milliamperes resistive load ac at sea level50.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0