

View Online at <https://aerobasegroup.com/nsn/5930-01-367-9343>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Overall Length:**

5.175 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Shaft Diameter:**

0.250 inches all actuators

**Shaft Length:**

0.688 inches all actuators

**Individual Section Quantity:**

6

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

8 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise all actuators

**Rotor Through Connection Quantity:**

8 each section

**Switch Actuator Indexing Position Quantity:**

8 all actuators

**Shaft Type:**

Round all actuators

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

50.0 milliamperes inductive load ac at sea level and 125.0 milliamperes resistive load ac at sea level 50.0 milliamperes inductive load dc at sea level and 500.0 milliamperes resistive load dc at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0