

View Online at <https://aerobasegroup.com/nsn/5930-01-368-3094>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

3.630 inches

Body Diameter:

1.200 inches

Bushing Length:

Between 1.482 inches and 1.654 inches

Body Length:

0.980 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.500 inches

Actuator Height:

1.082 inches

Actuator Free Position Height:

2.650 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

172.0 ounces

Switch Actuating Force:

172.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.500 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0