NSN 5930-01-368-8112

View Online at https://aerobasegroup.com/nsn/5930-01-368-8112

Toggle Switch - Page 1 of 2



Thread Class: 2b **Body Style:** Hole mount **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.625 inches **Body Length:** 0.830 inches **Body Width:** 0.718 inches **Body Height:** 1.820 inches **Actuator Style:** Rectangular **Actuator Width:** 0.648 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 28.0 dc and 115.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Panel and threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, three positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 15.000 amperes inductive dc and 8.000 amperes inductive ac and 5.000 amperes lamp dc and 2.000 amperes lamp ac and 18.000 amperes resistive dc and 11.000 amperes resistive ac **Thread Series Designator:** Unc **Terminal Type And Quantity:** 6 quick disconnect, male

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5930-01-368-8112 Toggle Switch - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A053a0