

View Online at <https://aerobasegroup.com/nsn/5930-01-368-8873>

**Hazardous Locations/environmental Protection:**

Dripproof

**Unthreaded Mounting Hole Diameter:**

0.203 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

2.300 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.300 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

125.0 ac at sea level30.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks, breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level10.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0