NSN 5930-01-369-1004

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-369-1004

| Thread Class: |
|--|
| 2a |
| Body Style: |
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Bushing Length: |
| Between 1.375 inches and 1.437 inches |
| Body Length: |
| 1.420 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.470 inches |
| Actuator Height: |
| 0.694 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thread Size: |
| 0.625 inches |
| Criticality Code Justification: |
| Feat |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes inductive dc and 4.000 amperes resistive dc and 4.000 amperes motor dc |
| Special Features: |
| Plunger, switch; hardness critical item |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 1 cable w/connector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |