

View Online at <https://aerobasegroup.com/nsn/5930-01-369-7561>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof

Overall Length:

3.060 inches

Overall Height:

Between 0.730 inches and 0.750 inches

Overall Width:

Between 0.730 inches and 0.750 inches

Body Width:

Between 0.730 inches and 0.750 inches

Body Height:

Between 0.730 inches and 0.750 inches

Case Material:

Metal

Actuator Length:

Between 0.730 inches and 0.750 inches

Actuator Style:

Rectangular

Actuator Width:

Between 0.730 inches and 0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator and yellow single actuator

Actuator Inscription:

On/off single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

Arleigh burke class ddg; mk46, mod 0 optical unit

Inclosure Type:

Uninclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding and lamp holder and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Weapon system essential; extra long ref number 80010a1c2d4j19l110m2n (wy) 16 on-off

Precious Material And Location:

Rfi screen surfaces gold

Terminal Type And Quantity:

12 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0