

View Online at <https://aerobasegroup.com/nsn/5930-01-369-7562>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof

**Overall Length:**

3.060 inches

**Overall Height:**

Between 0.730 inches and 0.750 inches

**Overall Width:**

Between 0.730 inches and 0.750 inches

**Body Width:**

Between 0.730 inches and 0.750 inches

**Body Height:**

Between 0.730 inches and 0.750 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.730 inches and 0.750 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

Between 0.730 inches and 0.750 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator and yellow single actuator

**Actuator Inscription:**

On/off single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding and lamp holder and horizontal split lens

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc

**Precious Material And Location:**

Rfi screen surfaces gold

**Terminal Type And Quantity:**

12 turret and 6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0