

View Online at <https://aerobasegroup.com/nsn/5930-01-369-7562>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof

Overall Length:

3.060 inches

Overall Height:

Between 0.730 inches and 0.750 inches

Overall Width:

Between 0.730 inches and 0.750 inches

Body Width:

Between 0.730 inches and 0.750 inches

Body Height:

Between 0.730 inches and 0.750 inches

Case Material:

Metal

Actuator Length:

Between 0.730 inches and 0.750 inches

Actuator Style:

Rectangular

Actuator Width:

Between 0.730 inches and 0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and yellow single actuator

Actuator Inscription:

On/off single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Uninclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding and lamp holder and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc

Precious Material And Location:

Rfi screen surfaces gold

Terminal Type And Quantity:

12 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0